## **LEAD LINED HOLLOW METAL DOOR FRAME - SINGLE SWING**

Customer:	A&L Sales Order #:			
Job Name:	Customer PO#			



JOD INA	inic.					Ot	astorner i	<del>- Οπ</del>				268 Old Lindale Road • Rome. GA 30161 706-235-8822 • FAX 706-232-2518	
Hinge .	/ Pivot:											700-233-0022 • FAX 700-232-2310	
Mfg.:			F	Reinforced for re	egular & paralle	el arm clos	ser						
Temp.							▎▎┌╇			_			
Temp.	#:									<u> </u>		Lead shielding in wall (extend into frame)	
Size:										ess.		<i>'</i>	
Gauge:							\ \ \ <u>\</u>	<u>II                                    </u>		dep lickn	. /	Lead shielding in frame	
Backse					C/L	of hinge	<b></b>			- Jamb depth - Wall thickness		Lead lined door	
Lock S	Strike									, ,			
Mfg.:										ļ <u>+</u> -l			
Temp.								<u> </u>					
Temp.	#:				C/L of hinge / i	nt. pivot		<u> </u>			TYPE 1 F		
Size:					J					Lead lined door is on the same side of wall as lead shielding			
	ock Strike			C/L of dead I	ock strike							-	
Mfg.:			<u>, î</u> ,					니니					
Temp.								<b>↓</b> ,⊥		<u> </u>		<b> </b>	
Temp.	#:				C/L of hinge / i	nt. pivot				- Lac			
Size:	N D - ' (		<del>     </del>	C/L of strike						Jamb depth		Lead lined door	
	Closer Reinfo	rcea	<del>                                      </del>							- Jamb depth - Wall thickness	M	Lead shielding in frame	
	b Face:							무				_	
Jaiii	о гасе.				C/L	of hinge		<u>V</u>		<u> </u>		Lead shielding in wall (extend into frame)	
											T)/DE 0.5	,	
			누	ᆛᅵ║						TYPE 2 FRAME			
											Lead lined door is on the opposite side of wall from lead shielding		
			<u> </u>										
Notes / F	Remarks:				Notes / Rema	rks:				Notes /	Remarks:		
1010071	tomanto.				rotoo / rtoma					1101007	rtomanto.		
Qty	Width	Height	JD	Wall Thk	Lead	Туре	Hand	Label	Gauge	Backbend	Rabbet	Tag #:	
•													
-													